

## Postfix: kako obrisati mailove iz queuea?



Postfix pomoćni program 'postsuper' (skraćeno od "postfix superintendent") je namijenjen za rad sa Postfix queuevima, odnosno mailovima u njima. Postsuper je namijenjen sistem administratorima, a ukoliko korisnici žele dio mogućnosti postsupera (npr. ispisati mail queue), trebaju rabiti naredbu 'postqueue'.

U većini slučajeva, postsuper će se rabiti za brisanje mailova iz queuea. U tu svrhu služi opcija -d:

```
# postsuper -d QUEUE_ID
```

Queue ID broj možete naći preko naredbe "postqueue -p", odnosno "mailq" (koju donosi postfix radi zadržavanja kompatibilnosti sa sendmailom).

```
# postqueue -p
-Queue ID- --Size-- ----Arrival Time---- -Sender/Recipient-----
F134C1838D      28300 Sun May 13 11:36:14 MAILER-DAEMON
      (connect to mail.pradella.biz[212.77.229.254]: Connection timed out)
      henry@pradella.biz

3C41518383      28352 Sat May 12 11:19:15 MAILER-DAEMON
      (connect to pistonheads.biz[195.225.218.139]: Connection timed out)
      john@pistonheads.biz

36FCE1838E      28328 Sat May 12 20:32:34 MAILER-DAEMON
      (connect to pistonheads.biz[195.225.218.139]: Connection timed out)
      john@pistonheads.biz

638221838B      28335 Sat May 12 18:06:48 MAILER-DAEMON
      (connect to 64.202.167.73[64.202.167.73]: Connection timed out)
      richard@guitarra.biz

-- 111 Kbytes in 4 Requests.
```

Kako ovo zna biti nepraktično, a počesto i sporo, donosimo kratku perl skriptu `delete_from_mailq.pl` koja će olakšati uporabu ove naredbe. Skriptu snimate primjerice u `/usr/sbin` (ili neki drugi direktorij koji je u `$PATH`-u root korisnika).

Uporaba je iznimno laka, jer kao parametar očekuje e-mail adresu, odnosno regularni izraz u obliku "spam.\*@domena.com", ".\*@spammerdomain.com" itd.).

E-mail adresa može biti i potpuna, primjerice "netko.negdje@domena.net".

Skripta `delete_from_mailq.pl` (možete je skinuti i [direktno](#) [1]):

```
#!/usr/bin/perl

$REGEXP = shift || die "no email-adress given (regexp-style, e.g.\
```

```
bl.*\@yahoo.com)!";

@data = qx</usr/sbin/postqueue -p>;
for (@data) {
    if (/^(\w+)(\*|\!)?\s/) {
        $queue_id = $1;
    }
    if($queue_id) {
        if ($REGEXP/i) {
            $Q{$queue_id} = 1;
            $queue_id = "";
        }
    }
}

open(POSTSUPER,"|postsuper -d -") || die "couldn't open postsuper" ;

foreach (keys %Q) {
    print POSTSUPER "$_\n";
};
close(POSTSUPER);
```

- [Logirajte](#) [2] se za dodavanje komentara

čet, 2007-05-17 14:46 - Željko Boroš**Kuharice:** [Za sistemce](#) [3]

**Kategorije:** [Servisi](#) [4]

**Vote:** 0

No votes yet

**Source URL:** <https://sysportal.carnet.hr/node/203>

#### Links

[1] [https://sysportal.carnet.hr/system/files/delete-from-mailq.pl\\_.txt](https://sysportal.carnet.hr/system/files/delete-from-mailq.pl_.txt)

[2] <https://sysportal.carnet.hr/sysportallogin>

[3] <https://sysportal.carnet.hr/taxonomy/term/22>

[4] <https://sysportal.carnet.hr/taxonomy/term/28>